




Product Name	File No.	Version	Date	Page
BL-0210 Reed Switches	BL-3D-062	A3	2019.11.15	1/3

- Ideal for ATE switching and proximity sensors
- Contact layers: Ruthenium on gold
- Superior glass-to-metal seal and blade alignment
- Excellent life expectancy and reliability
- RoHS Compliant



1. Automation Device
2. **Home appliances and**
3. Auto industry
4. Communication
5. Medical

The switch may be actuated by an electromagnet, a permanent magnet or a combination of both. The device is intended for use in sensors, relays, pulse counters or similar devices.



Http://www.blswitch.com E-mail:dgbailin@126.com

Product Details specification

Product Name	File No.	Version	Date	Page
Reed Switches BL-0210	BL-3D-062	A3	2019.11.15	2/3

■ Electrical characteristics:

DATA SCAN	单位 Unit	BL-0210
Contact Fom		A
Contact Rating	W	10
Switching Voltage	VDC	100
Breakdown Voltge	VDC	150
Switching Current	A	0.5
Carry Current	A	
Intial Contact Resistance	MΩ	100
Insulation Resistance	Ω	10 ⁹
Operating Time	Ms	0.5
Bounce Time	Ms	0.2
Release Time	Ms	0.3
Hesonant Frequency	Hz	5000
Operating Frequency	Hz	400
Pull In Value	AT	10-35
Drop Out Value	FT	4
Contact Capacitance	PT	0.3
Electrcal Life(Resistive Loads)		5X10 ⁶ (5Vdc,10mA)10 ⁶ (24Vdc,250mA)
Test Coll Number Of Turns Resistance	Ω	5000 580

■ Welding characteristics


Manual welding : 330°C±10°C, 2-3

■ Packaging:

200PCS/Bag (PVC plastic bag, according to the general electronic material storage requirements)

■ SIZE尺寸

Unit=mm



地址：东莞市万江区拔蛟窝苏屋工业区

Add: Suwu Industrial Zone, Bajiaowo Village, Wangjiang District, Dongguan, Guangdong

TEL: 86+769+22176561 Fax: 86+769+22778617

Http://www.blswitch.com E-mail: dgbailin@126.com